



DJ EFFECTOR

DPH-X1

OWNER'S MANUAL

Vestax Corporation

1-18-6 Wakabayashi Setagaya-ku Tokyo 154-0023 Japan.

Phone 03-3412-7011, Fax 03-3412-7013

Web : www.vestax.co.jp

Vestax (Europe) Ltd.

Unit 5 Riverwey Industrial Park Alton Hampshire GU34 2QL England, U.K.

Phone (0)1420-83000, Fax (0)1420-80040

Web : www.vestax.co.uk

Vestax America (west Corst)

15320 Valley View Road Unit 9 La Mirada, CA 90638

Phone (562)623-9881, Fax (562)483-7304

Web : www.vestaxdj.com

CONGRATULATIONS!

Thank you for purchasing the VESTAX DPH-X1 Ultra Phaser.
Please read this owner's manual carefully before you start to use your
DPH-X1 in order to fully understand all of the special features.

CONTENTS

| | |
|----------------------------|---|
| CAUTION | 1 |
| IMPORTANT SAFEGUARDS | 2 |
| FEATURES | 3 |
| FUNCTIONS | 3 |
| CONNECTION DIAGRAM | 5 |
| SETTING EXAMPLES | 5 |
| SPECIFICATIONS | 6 |



CAUTION



RISK OF ELECTRIC SHOCK DO NOT OPEN

CAUTION : TO REDUCE THE RISK OF ELECTRIC SHOCK
DO NOT REMOVE COVER (OR BACK)
NO USER-SERVICEABLE PARTS INSIDE
REFER SERVICING TO QUALIFIED SERVICE PERSONNEL



The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, DO NOT
EXPOSE THIS APPLIANCE TO RAIN OR MOISTURE.

CAUTION : TO PREVENT ELECTRIC SHOCK, MATCH BLADE OF
PLUG TO WIDE SLOT, FULLY INSERT

ATTENTION : POUR EVITER LES CHOCS ELECTRIQUES,
INTRODUIRE LA LAME LA PLUS LARGE DE LA
FICHE DANS LA BORNE CORRESPONDANTE DE LA
PRISE ET POUSSER JUSQU' AU FOND

IMPORTANT SAFEGUARDS

READ BEFORE OPERATING EQUIPMENT

This product was designed and manufactured to meet strict quality and safety standards. There are, however, some installation and operation precautions which you should be particularly aware of.

1. Read Instructions-All the safety and operating instructions should be read before the appliance is operated.
2. Retain Instructions-The safety and operating instructions should be retained for future reference.
3. Heed Warnings-All warnings on the appliance and in the operating instructions should be adhered to.
4. Follow Instructions-All operating and use instructions should be followed.
5. Cleaning-Unplug this product from the wall outlet before cleaning. Do not use liquid cleaners or aerosol cleaners. Use a damp cloth for cleaning.
6. Attachments-Do not use attachments not recommended by the product manufacturer as they may cause hazards.
7. Water and Moisture-Do not use this product near water-for example, near a bath tub, wash bowl, kitchen sink, or laundry tub, in wet basement, or near a swimming pool, and the like.
8. Accessories-Do not place this product on an unstable surface. The product may fall, causing serious injury to child or adult, and serious damage to the appliance. Use only with a surface, or table recommended by the manufacturer, or sold with product. Any mounting of the appliance should follow the manufacturer's instructions, and should use a mounting accessory recommended by manufacturer.
9. Ventilation-Slots and openings in the cabinet are provided for ventilation, to ensure reliable operation of the product and to protect it from overheating, and these openings must not be blocked or covered. The unit should never be placed on an uneven surface(eg. bed) during operation. This product should never be placed near or over a radiator or heat register. This product should not be placed in a built-in installation such as a bookcase or rack unless proper ventilation is provided or the manufacturer's instructions have been adhered to.
10. Power sources-This product should be operated only from the type of power source indicated on the marking label. If you are not sure of the type of power supply to your home, consult your appliance dealer or local power company.
11. Grounding or Polarization-This product is equipped with a polarized alternating-current line plug (a plug having one blade wider than the other). This plug will fit into the power outlet only one way. This is safety feature. If you are unable to insert the plug fully into the outlet, try reversing the plug. If this should still fail to fit, contact your electrician to replace your obsolete outlet. Do not defeat the safety purpose of the polarized plug.
12. Power-Cord Protection-Power supply cords should be routed so that they are not likely to be walked on or squashed by items placed upon or against them, paying particular attention to cords at plugs, convenience receptacles, and the point where they exit from the appliance.
13. Protective Attachment Plug-The appliance is equipped with an attachment plug having overload protection. This is a safety feature. See Instruction Manual for replacement or resetting of protective device. If replacement of the plug is required, be sure the service technician has used a replacement plug specified by the original plug.
14. Lightning-For added protection of this product during a lightning storm, or when it is left unattended and unused for long periods of time, unplug it from the wall outlet. This will prevent damage to the product due to lightning and power-line surges.
15. Overloading-Do not overload wall outlets and extension cords as this can result in a risk of fire or electric shock.
16. Object and Liquid Entry-Never push objects of any kind into this product through openings as they may touch dangerous voltage points or short-out parts that could result in a fire or electric shock. Never spill liquid of any kind on the product.
17. Servicing-Do not attempt to service product yourself as opening or removing covers may expose you to dangerous voltage or other hazards. Refer all servicing to qualified personnel.
18. Damage Requiring Service-Unplug this product from the wall outlet and refer servicing to qualified service personnel under the following conditions:
 - a. When the power-supply cord or plug is damage.
 - b. If liquid has been spilled or objects have fallen into the product.
 - c. If the product has been exposed to rain or water.
 - d. If the product does not operate normally by following the operating instructions. Adjust only those controls that are covered by the operating instructions as an improper adjustment of other, controls may result in damage and will often require extensive work by a qualified technician to restore the product to its normal operation.
 - e. If the product has been dropped or cabinet has been damaged.
 - f. When the product exhibits a distinct change in performance-this indicates need for service.

19.Replacement Parts-When replacement parts are required, be sure the service technician has used replacement parts specified by the manufacturer or which have the same characteristics as the original parts. Unauthorized substitutions may result in fire, electric shock or other hazards.

20.Safety Check-Upon completion of any service or repairs to this product, ask the service technician to perform safety checks to determine that the product is in proper operating condition.

21.Carts and Stands-The appliance should be used only with a cart stand that is recommended by the manufacturer.

22.An appliance and cart combination should be moved with care. Quick stops, excessive force, and uneven surfaces may cause the appliance and cart combination to overturn.




FEATURES

- 12-step phase shifting circuit allowing DJs to create an extremely wide range effect.
- Bypass / Effect Crossfader allows the user to instantly switch or move between dry sound or effect sound in one smooth “crossfade” action. The best mix of dry + effect sound can also easily be selected.
- Input select switch (PHONO/LINE/CD) offers direct connection possibilities with almost any audio equipment. The DPH-X1 can also be connected between the turntable or the CD player and the mixer if the mixer has an effect loop facility ; or between the mixer and the power amplifier if no effects loop facility is available.
- The unique 1U half-rack size is perfect for many applications. The depth of the DPH-X1 is of similar height to a turntable, so it can easily be utilized vertically in a quick set up. Vestax offer a 19" rack frame with two spaces to rack the DPH-X1 alone, or together with other Vestax half rack series effects.

FUNCTIONS

FRONT PANEL



① POWER INDICATOR

LED will light when the power is on.

② MIX CONTROL

Slide to the left, EFFECT is active.
Slide to the right, NORMAL is active.
In the center position, mix of both.

③ PHASE MODE SELECT SWITCH

This switch is to select 3 types of phase mode.

- (a) MONO PEAK -Single Peak type shifter to create dynamic phasing sound.
- (b) MONO DIP -Single Dip type shifter to create natural phasing sound.
- (c) STEREO DIP -Stereo Dip type phase shifter to create ambient sound.

④ PHASE SHIFT SELECT SWITCH

Select the range of how deep the phase sound is out of 2, 4, 6, 8, 10, 12 steps.

⑤ BIAS CONTROL (AUTO MODE ONLY)

The center of the frequency band in a shifted signal can be moved from 10kHz to 100Hz and the LFO effect will be active according to the setting.

⑥ DEPTH CONTROL (AUTO MODE ONLY)

This is to control the width of phasing from wide to narrow. It adjusts the depth of modulation of the phase sound.

⑦ SPEED CONTROL (AUTO MODE ONLY)

This is to control the speed of phasing from fast to slow. It adjusts the speed of the modulation of the phase sound.


⑧ AUTO / MANUAL SELECT SWITCH

Push in to activate AUTO MODE.

⑨ MANUAL CONTROL

For manual manipulation of the phase sound based on the settings (3),(4).

SIDE PANEL



⑩ INPUT SELECT SWITCH

PHONO(-46dB) / LINE(-10dB) / CD(0dB)

⑪ OUTPUT JACK [RCA pin jack]

⑫ INPUT JACK [RCA pin jack]


⑬ GND TERMINAL

Connect the ground cable here.

⑭ DC JACK

Vestax Adaptor DC-15V.


CONNECTION DIAGRAM



SETTING EXAMPLES


1. PHASER SOUND (for ALL GENRE)

Typical 4 step jet swing sound.




2. "LULL PHASER" SOUND (for Ambient)

12 step clear and delicate phase sound.




3. "DYNAMIC PHASE" SOUND (for HIP HOP / R&B)

Peaking type phaser just like dynamic filtering.




4. AUTO PAN TYPE STEREO PHASE (for ALL GENRE)

Auto panning stereo phase sound.



5. SURROUND STEREO PHASE (for HOUSE / TRANCE)

Create circling sound.



SPECIFICATIONS

| | |
|------------------------|--|
| TYPE | ULTRA PHASER |
| NOMINAL INPUT LEVEL | PHONO -46 dB LINE -10 dB CD 0 dB |
| NOMINAL OUTPUT LEVEL | -10 dB (NORMAL) |
| S/N RATIO | -70 dB (NORMAL) |
| POWER SUPPLY | DC 15V |
| DIMENSIONS (W × H × D) | 218 × 44 × 103 (mm) |
| WEIGHT | 645 (g) |





Vestax Corporation 1-18-6 Wakabayashi, Setagaya-ku, Tokyo 154-0023 Japan
Telephone : 81-(0)3-3412-7011 Fax : 81-(0)3-3412-7013. www.vestax.jp

**This is to certify that the product subsequently referred to
was designed and manufactured in conformity with the
following EC directives;
89/336/EEC (EMC)
73/23/EEC (LVD)**

Model type : Professional DJ Effector

Model Description : Half rack size / DJ Effector series

Model Number : DPH-X1

Applicable Standards : EN55013:1990+A12:1994+A13:1996 Limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment (including amendments A12:1994 and A13:1996) (CISPR13:1975/Amdt1:1983, modified)
EN50082-1:1997 Electromagnetic compatibility-Generic immunity standard Part1:Residential, commercial and light industry

Date : Wednesday, December 19, 2001

Place of Issue : Vestax Corporation, 1-18-6 Wakabayashi, Setagaya-ku,
Tokyo 154-0023 Japan

**Manufacturers Authorized
Signature :**

Function of Signatory :

Masaaki Shiomi

Director